



INTERMARINE

INTERFLOAT

Continuous flotation concrete decked walkways make this range an exceptionally robust pontoon system.

The Interfloat is designed for projects where an exceptionally stable or high live load capacity is required.

STRUCTURE

The pontoons have a reinforced concrete structure with integral expanded polystyrene buoyancy. Reinforcement near the surface may be galvanised.

PROTECTION OF BASE

Pontoons can be supplied with textile or painted protection to the polystyrene base of the units. Alternative heavier duty treatments can be supplied where required.

CONNECTIONS

The units are connected end to end with flexible connections comprising M37 galvanised bolts and rubber bushes. Units may be connected side to end by prior design.

FENDERS

Walkways are fitted as standard with 145mmx70mm softwood fenders.

LIFTING POINTS

For safe handling built in lifting points are included in all units.

SERVICE DUCTS

Ducts may be built into units to suit service requirements.

OPTIONAL UNIQUE FEATURES

Features such as continuous finger adjustment and top access service ducts that are normally only associated with metallic or timber systems can be incorporated into the design.

MOORING OPTIONS

The pontoons may be fixed by piles or flexible moorings. Standard pile guides are available for tubular piles. Guides are provided with low friction lining and have universal longitudinal adjustment. Special guides for use with other types of pile can be supplied.

4 kN/m reserve buoyancy

500mm unladen freeboard

2.46m or 2.96m width walkway units available

Compatible with Atlantic fingers and fixings

Universal finger connection (optional)

Optional service duct

Pontoon base protection

Timber fender



INTERFLOAT

STANDARD UNITS

	LENGTH	WIDTH
AP0	12	2.96
AP1	12	2.46

Measurements in metres



Intermarine Ltd practises a policy of continuous development and reserves the right to alter specifications without notice.



Intermarine Limited

Equity Court, 73-75 Millbrook Road East,
Southampton, Hants SO15 1RJ, UK

Tel: +44 (0)23 8023 1332
Fax: +44 (0)23 8033 7721

E-mail: pontoons@intermarine.co.uk
Website: www.intermarine.co.uk